

HIGH QUALITY PHOTO PAPERS

mediaJET® SIP 260 Silver Iridium Pearl | Photo paper with pearlescent effect

Product description

Silver iridescent photo paper, which emphasizes the effect of metallic picture elements impressively and uniquely. Jewellery, industrial motifs and portraits are particularly striking thanks to their high density and maximum colour space. The fascinating metallic effects and an iridescent shimmer on this extraordinary pearl photo paper will win you over.

Specific feature

mediaJET SIP 260 Silver Iridium Pearl is a newly developed photo paper, with a special iridescent lustre ink jet coating. With its metallic-pearl surface, the paper is ideal for photos where the metal character is to be emphasized, and for black and white/portrait photography, where special iridescent effects are desired. Photo-realistic, true-colour, lively and detailed reproductions, printed up to 5760dpi, with the feel of a classic photo paper are the result. mediaJET SIP 260 Silver Iridium Pearl is a high quality photo paper, suitable for universal application on all current LFP-ink jet printers with dye and pigment inks. The nano-porous coating delivers excellent, highly detailed colour rendering, with sharp contours, an extremely large colour gamut and excellent flatness.

Processing

To guarantee optimal quality, photo and fine art papers should be stored and processed in a climate with 30-70% relative humidity and at temperatures from 15-30°C. We recommend that the paper be acclimatised in the print room for one day before printing, and to reseal in the original package after printing. Prevent fingerprints on the coated side by wearing clean cotton gloves while processing. Please avoid contact with solvent, glue and softener, leads to yellowing.

Technical specification			
Material:	Paper	Colour L:	89,75
Application Area:	only indoor	Colour a:	0,00
Surface:	Lustre	Colour b:	-4,10
Specific gravity:	260,00g/m ²	Whiteness (R457) (ISO 11475):	81 ± 2 %
Thickness:	270,00µm	Specular gloss (ISO 8254-1):	56 ± 5 %
B1-cert.:	no	Opacity (ISO 2471):	96 ± 4 %
Cold lamination:	yes		
Heat lamination:	yes	DIN ISO 16245:	no

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We not accept liability for any errors resulting from technical changes in printers and / or inks.