

DELICATE FINEART PAPERS

mediaJET® Museum Fibre matt | Natural white photo-art paper

Product description

Natural white, velvety soft photo art paper made of 100% alpha cellulose, with a fibre surface based on the classic rag paper. The light paper is FOGRA certified, acid-free and coated without optical brightener. Enables prints with high D-Max value and dynamic colour reproduction, ideal for exhibitions, competitions, photo and fine-art work.

Specific feature

mediaJET Museum Fibre matt is characterised by its velvety-soft, warm tone white surface that gives the impression of a classic, cotton paper. Made of 100% alpha pulp, mediaJET Museum Fibre matt is lignin- and acid-free. The complete absence of optical brightener results in an attractive, natural white paper tone. Designed with an eye on the demanding and price-conscious users, it is ideally suited for photographic and photo-realistic applications such as the decoration of exhibition areas but also for architectural competitions, advertising material, greetings cards, calendars, etc. Thanks to the latest coating technology, it is possible to achieve a harmonious, yet powerfully dynamic colour reproduction, the highest D-Max values and an accurate picture definition on a very wide range of print systems, using both pigmented and dye-based inks. At the same time, the result is a stable, uniform and high paper quality with a dust-free print surface.

Processing

To guarantee optimal quality, photo and fine art papers should be stored and processed in a climate with 30-70% relative humidity and at temperatures from 15-30°C. We recommend that the paper be acclimatised in the print room for one day before printing, and to reseal in the original package after printing. Prevent fingerprints on the coated side by wearing clean cotton gloves while processing. Please avoid contact with solvent, glue and softener, leads to yellowing.

Technical specification			
Material:	Paper	Colour L:	98,7
Application Area:	only indoor	Colour a:	-0,7 yes
Surface:	matt	Colour b:	1,75
Specific gravity:	200,00g/m ²	Whiteness (R457):	> 80% (D65/10°)
Thickness:	300,00µm	Opacity:	> 94%
B1-cert.:	no	Water resistant:	yes
Cold lamination:	yes	DIN ISO 9706 archive-resistant:	yes
Heat lamination:	yes	DIN ISO 16245:	no

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We not accept liability for any errors resulting from technical changes in printers and / or inks.