

mediaJET® PMC 260FD “premium” | Silk matt photo paper FastDry

Product description

The pleasant, slightly warm hue of this paper perfectly captures skin tones and makes a warm, classic impression; the excellent image sharpness and colour reproduction combined with extended colour space and fast drying guarantee first-class printing results on this silk-like paper.

Specific feature

Universally applicable weighty photo satin paper with a silky-matte surface which shows a practically immediate smearless drying and excellent water resistance. Colour images are reproduced in an almost photo-realistic way, true colours, living and rich in detail. mediaJET PMC 260FD Premium is a high-quality photo paper for the universal use on all common LFP inkjet plotters using dye-based as well as pigmented inks. The coating of this genuine photo basic paper shows an excellent colour reproduction at high truth of detail, sharpness of outline, an extreme great colour complexity and excellent flatness. mediaJET PMC 260FD Premium is an inkjet paper for highest requirements. The silk matte mediaJET PMC 260FD Premium with high resolution can be laminated cold. Due to its robust surface in many cases lamination is not necessary when used in the indoor area.

Processing

To guarantee optimal quality, photo and fine art papers should be stored and processed in a climate with 30-70% relative humidity and at temperatures from 15-30°C. We recommend that the paper be acclimatised in the print room for one day before printing, and to reseal in the original package after printing. Prevent fingerprints on the coated side by wearing clean cotton gloves while processing. Please avoid contact with solvent, glue and softener, leads to yellowing.

Technical specification

Material:	Paper	Colour L:	95,95
Application Area:	only indoor	Colour a:	0,00
Surface:	silk matt	Colour b:	-2,9
Specific gravity:	260,00g/m ²	Whiteness (R457) (ISO 2470):	92 ± 3 %
Thickness:	265,00µm	Specular gloss (ISO 8254-1):	47 ± 0,5 %
B1-cert.:	no	Smoothness (Bekk) (ISO 5627):	>750 sec
Water resistant:	no	Rigidity md (ISO 2493)	2,3mN ± 0,8
Cold lamination:	yes	Rigidity cd (ISO 2493)	1,45mN ± 0,8
Opacity (ISO 2471):	96 ± 4 %	DIN ISO 16245:	no

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We not accept liability for any errors resulting from technical changes in printers and / or inks.