

## mediaJET® PhotoArt White Satin | Fourdrinier photo-art inkjet paper

---

### Product description

This PhotoArt paper full of character with a pleasantly grippy rag surface is bright white, with little optical brightener and made of 100%  $\alpha$ -cellulose. Printed surfaces, such as photos, graphics and drawings, are reproduced with a silk-matt effect; unprinted surfaces remain unobtrusively matt. This paper opens up new possibilities for photographers and artists and gives the print brilliance and dynamism.

### Specific feature

Finished on a fourdrinier machine, mediaJET PhotoArt White Satin was created for digital applications with the structure, the feel and the beauty of traditional materials. It is characterized by the velvety soft, white surface and is made of 100%  $\alpha$ -cellulose, making it well suited for photo applications and photorealistic renditions. mediaJET PhotoArt White Satin distinguishes itself from other FineArt media through its satin inkjet coating. It was created for the high-quality requirements of the demanding user. With mediaJET PhotoArt White Satin harmonious color intensity and exact sharpness can be attained using pigment or dye inks and on all print systems. This FineArt paper was made according to the DIN 6738 / ISO 9706 norms for archival paper.

### Processing

To guarantee optimal quality, photo and fine art papers should be stored and processed in a climate with 30-70% relative humidity and at temperatures from 15-30°C. We recommend that the paper be acclimatised in the print room for one day before printing, and to reseal in the original package after printing. Prevent fingerprints on the coated side by wearing clean cotton gloves while processing. Please avoid contact with solvent, glue and softener, leads to yellowing.

---

### Technical specification

---

Material:	Paper	Colour L:	98,80
Application Area:	only indoor	Colour a:	1,15
Surface:	Silk Matt	Colour b:	-4,30
Specific gravity:	270,00g/m <sup>2</sup>	UV Whiteness:	91% (ISO 11475)
B1-cert.:	no	PH Value:	8,0 (DIN 53124)
Cold lamination:	yes	DIN ISO 9706 archive-resistant:	yes
Opacity:	97% (DIN 53146)	DIN ISO 16245:	no

---

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We not accept liability for any errors resulting from technical changes in printers and / or inks.